

iQ500-RP INTELLIGENT REPEATER PANEL



Product Overview:

The iQ500-RP intelligent addressable repeater panel is a cost effective way to provide system status information in key remote areas, away from control panel. It is easily connected to the panel through RS485 communication port.

Features:

- As per UL 864, 9th Edition & NFPA 72.
- 32 bit processor Arm Cortex M3.
- 160 (40X4) character LCD display.
- Real Time Clock.



Network options:

- RS 485 Communication for Network/Repeater.
- USB 2.0 Interface for PC Connectivity.
- One form C relay for Fire.
- Extensive, built-in transient protection.
- Lamp test Facility.

Electrical Specification:

Operating Power

24V D.C.

Operating Condition

Operating Temperature 0 - 49° C/32-120° F.


Relative Humidity 93 ± 2% RH (non-condensing) at 32 ± 2° C/96 ± 3° F.

One Common Form C Relays


Relay Contact Rating: 2A @ 30 VDC, 2A @ 30VAC.

Power Factor: 1.0


G.A.Diagram:



Mounting Detail:



Terminal Details:



Fireguard safety equipment co Ltd.,

145-157 St. John Street,
London EC1V 4PY, United Kingdom.

Web: www.fireguard-uk.com

Email: info@fireguard-uk.com